

# SG18-3

Leveling the playing field between performance and value

- ▶ Engine model: Cummins 6BTAA5.9-C180
- ▶ Rated power: 132 kW/2200 rpm
- ▶ Operating weight: 16.2 t

## Product features

This third generation grader is a smart value in Shantui's diversified product lineup. It comes standard with a Cummins engine and articulated steering for greatly increased turning radius, with more flexible operation resulting. It can "crabwalk" when called upon to avoid tracking over leveled areas. And best of all, Shantui graders come with an excellent field of vision, allowing the operator to view all the working components both in front and behind the cab.



shantui e-shop

# SHANTUI

VALUE THAT WORKS

Shantui Construction Machinery Co., Ltd.

ADDRESS:  
No. 58, G327 Highway  
Jining City, Shandong, CHINA


TEL: +86-537-2909369  
FAX: +86-537-2311219  
EMAIL: trade@shantui.com


# SG18-3


## Technical specifications:


Operating weight: 16.2 t	Gradeability: 20°
Blade length: 3660/3965 mm	Wheel base: 6260 mm
Minimum ground clearance: 430 mm	Maximum traction: 91 kN


SG18-3

	ENGINE	Engine model	Cummins 6BTAA5.9-C180				
		Engine type	In-line, water-cooled, 4-cycle, direct injection, turbocharged				
		Rated power/speed	132 kW/2200 rpm				
		Number of cylinders (bore x stroke)	6 (102 x 120 mm)				
		Piston displacement	5.9 L				
		Maximum torque/speed	770 N-m/1500 rpm				
		Minimum fuel consumption	206 g/kW-h				

	TRAVEL SPEED	Transmission and torque converter: Electronic controlled transmission with 6 forward gears and 3 reverse gears.						
		Gear	1st	2nd	3rd	4th	5th	6th
		Forward	0~5.4 km/h	0~9.3 km/h	0~12.2 km/h	0~20.7 km/h	0~25.6 km/h	0~39.7 km/h
		Reverse	0~5.4 km/h	0~12.2 km/h	0~25.6 km/h	-	-	-

	SYSTEMS	Balance box	Type	No-spin limited slip differential, heavy-duty roller chain drive		
			Oscillation angle	15° forward, 15° reverse		
		Tire	Type	17.5-25PR12		
			Pattern level	E-3/L-3		
			Optional tire	17.5-25PR12		
		Steering system	Minimum turning radius	7800 mm		
			Front wheel tilting angle	±17°		
			Front wheel steering angle	±45°		
			Front axle oscillating angle	±15°		
		Brake system	Articulation angle	±25°		
			Service brake	4-wheel pliers-pan brake, full hydraulic, foot brake		
			Parking brake	Hand brake with ratchet wheel		
		Operating weight	Brake pressure	10 MPa		
Total	16200 kg					
Front axle load	4800 kg					
	Rear axle load	11400 kg				

	BLADE	Blade length	3660/3965 mm		
		Blade height	635 mm		
		Blade rotational angle	360°		
		Cutting angle adjustment range	44~91°		
		Maximum cutting depth	500 mm		
		Cutting force per dozing	24.47kN/m		
		Maximum lift above ground	440 mm		
		Maximum blade lateral extension (left/right)	1900/1950 mm		

	HYDRAULIC SYSTEM	Working pump	Tandem pump		
		Displacement of working pump	28*2ml/r		
		Working hydraulic pressure	16 MPa		

## OVERALL DIMENSIONS

▶ THE SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE. THE PICTURES MAY INCLUDE OPTIONS. THE ACTUAL COLOR & APPEARANCE OF THE PRODUCT MAY DIFFER FROM WHAT IS SHOWN.

